

Capital Tape Co, Inc
4920 Commerce Parkway #11
Cleveland, OH 44128
Fax: 887-893-3337



4400 Series Water Clear Acrylic Foam – White Liner

Water clear, solid acrylic tape designed to provide superior bond between a wide variety of surfaces. This product was developed for applications where clarity is important. The tape exhibits excellent performance under a wide range of environmental conditions including exposure to fuels and chemicals.

FEATURES:

- Long life performance and high bond strength
- Flexible, moldable, compressible – conforms to intricate shapes
- Will not absorb moisture
- Maintains adhesion at sub-zero temperatures

BENEFITS:

- Instant pressure sensitive bonding
- Will not harden or become brittle with age
- Excellent weathering properties; non-staining after aged contact
- Isolates and dampens vibration and shock
- Maintains adhesion from -30°F to 200°F

TECHNICAL DATA:

Tape thickness	0.010", 0.020", 0.025", 0.030", 0.040", and 0.060"	
Tensile Strength	ASTM D412 Die C	150 psi
Elongation	ASTM D412 Die C	1000%
Peel Adhesion	ASTM D3330	10 pli
90° Peel Strength	ASTM D1062	20 psi
Dynamic Shear Strength	ASMT D3163	60 psi
Installation Temperature Range	50°F - 100°F	
Service Temperature Range	-30°F -200°F	

These are approximate values and do not constitute warranty that products are fit for a particular purpose. The customer is advised to fully determine the suitability of these products for his intended use. These products conform to published specifications, if any, and the products are merchantable. Test data contained herein is believed to be reliable but unless specifically stated are not to be taken as specifications for products.

May2002