

Capital Tape Co, Inc  
4920 Commerce Parkway #11  
Cleveland, OH 44128  
Fax: 887-893-3337



## Capital Tape 5200 Series

Flexible polyethylene foam coated two sides with a high tack, acrylic adhesive protected by a plastic liner. Long term bonding performance in indoor and outdoor applications.

### Physical Properties:

Thickness & Density: 1/8" thick, 2# /cubic foot density  
1/16" thick, 4#/ cubic foot density

Water Absorption <1.0%

Water Penetration <1.0%

#### Tensile Adhesion (Average of 3 tests)

a. 77° ± 5° F	368.2% with 74.8 psi
b. 120° ± 5°F	301.5% with 52.4 psi
c. 32° ± 5° F	360.6% with 92.8 psi

#### Peel Adhesion (Average of 3 tests)

	Aluminum	Glass
a. 120°± 5°F	8.5 lb./in. width	3.9 lb./in. width
b. 32° ± 5° F	12.2 lb./in. width	3.0 lb./in. width

Suggested Application Temperature: 50° F (minimum) \*

These are approximate values and do not constitute a warranty. It is the customer's responsibility to determine these products' fitness for his intended use. These products conform to published specifications, if any, and the products are merchantable. Test data contained herein is believed to be reliable but unless specifically stated are not to be taken as specifications for products.