

Capital Tape Co, Inc
4920 Commerce Parkway #11
Cleveland, OH 44128
Fax: 887-893-3337



9226BKHS

PRODUCT DESCRIPTION:

Closed cell, 1/16" thick polyethylene foam coated on both sides with a permanent, specially formulated higher shear adhesive. The adhesives are protected by an 80# densified kraft liner. Excellent adhesion to painted metal surfaces; conformity to irregular surfaces.

PERFORMANCE DATA:

180° Peel Adhesion	PSTC-3	Adhesive strength exceeds the internal strength of the foam
Tensile Strength MD CD	ASTM D-3575T	4.68 US lbs/1" width 4.06 US lbs/1" width
Elongation CD/MD	ASTM D-3575T	290%
Polyken Tack (100 g/cm, 1 sec. dwell, 0/1 cm/sec separation rate)	Polyken Probe	500 grams
Shear Adhesion	PSTC-7	168 hours
Service Temperature Range	-40°F to 190°F	

These are approximate values and do not constitute warranty that products are fit for a particular purpose. The customer is advised to fully determine the suitability of these products for his intended use. These products conform to published specifications, if any, and the products are merchantable. Test data contained herein is believed to be reliable but unless specifically stated are not to be taken as specifications for products.