

**Capital Tape Co, Inc**  
**4920 Commerce Parkway #11**  
**Cleveland, OH 44128**  
**Fax: 887-893-3337**



## **9228 (White) / 9228BK (Black) Foam Tape – Rubber Adhesive**

### **PRODUCT DESCRIPTION:**

Closed cell , 1/8" polyethylene foam , black or white, coated both sides with a permanent, rubber-based adhesive. The adhesives are protected by a durable, polycoated densified kraft liner. This liner is specifically designed to provide tear resistance and easy removability.

### **PHYSICAL PROPERTIES:**

180° Peel Adhesion (30 minutes dwell on stainless steel)	120 oz./in. of width
Loop Tack	9 lbs.
Polyken Tack (100 g/cm, 1 second dwell, 0/1 cm/sec separation rate)	800 grams
Shear Resistance (90°F, 2 lbs. load)	1 square inch – 300+ hours ¼ square inch – 1 hour
Application Range	40° F to 150°F
Service Temperature Range	0°F to 150°F

These are approximate values and do not constitute warranty that products are fit for a particular purpose. The customer is advised to fully determine the suitability of these products for his intended use. These products conform to published specifications, if any, and the products are merchantable. Test data contained herein is believed to be reliable but unless specifically stated are not to be taken as specifications for products.