

Capital Tape Co, Inc
4920 Commerce Parkway #11
Cleveland, OH 44128
Fax: 887-893-3337



9233 (White) / 9233BK (Black) Foam Tape – Acrylic Adhesive

PRODUCT DESCRIPTION:

Closed cell, 1/32" polyethylene foam , black or white, coated both sides with a general purpose acrylic adhesive, protected by a durable paper liner.

PHYSICAL PROPERTIES:

| | | |
|--|-------------|-------------------|
| Density | | 6 lbs/ cubic inch |
| Tensile Strength | ASTM D-3575 | 6 lbs/ inch |
| Elongation | ASTM D-3575 | 250% |
| 180° Peel Adhesion, stainless steel | | |
| Liner Side | PSTC-3 | 80 oz./inch |
| Face Side | | 80 oz./inch |
| Compression Strength | | |
| @ 25% | ASTM D-3575 | 17 p.s.i. |
| @50% | | 32 p.s.i. |
| Tear Resistance | | |
| MD | ASTM D-3575 | 50 lbs./ inch |
| CD | ASTM D-3575 | 39 lbs./ inch |
| Compression Set (% of original thickness) | ASTM D-3575 | 8% |
| Application Range | | 40° F to 100°F |
| Service Temperature Range | | 0°F to 180°F |

These are approximate values and do not constitute warranty that products are fit for a particular purpose. The customer is advised to fully determine the suitability of these products for his intended use. These products conform to published specifications, if any, and the products are merchantable. Test data contained herein is believed to be reliable but unless specifically stated are not to be taken as specifications for products.