

**Capital Tape Co, Inc**  
**4920 Commerce Parkway #11**  
**Cleveland, OH 44128**  
**Fax: 887-893-3337**



## **9236 (White) / 9236BK (Black) Foam Tape – Acrylic Adhesive**

### **PRODUCT DESCRIPTION:**

Closed cell , 1/16" polyethylene foam , black or white, coated both sides with a general purpose acrylic adhesive, protected by a durable paper liner.

### **PHYSICAL PROPERTIES:**

Density		4 lbs/ cubic inch
Tensile Strength	ASTM D-3575	8 lbs/ inch
Elongation	ASTM D-3575	200%
180° Peel Adhesion, stainless steel		
Liner Side	PSTC-3	80 oz./inch
Face Side		80 oz./inch
Compression Strength		
@ 25%	ASTM D-3575	11 p.s.i.
@50%		22 p.s.i.
Tear Resistance		
MD	ASTM D-3575	31 lbs./ inch
CD	ASTM D-3575	23 lbs./ inch
Compression Set (% of original thickness)	ASTM D-3575	13%
Application Range		40° F to 100°F
Service Temperature Range		0°F to 180°F

These are approximate values and do not constitute warranty that products are fit for a particular purpose. The customer is advised to fully determine the suitability of these products for his intended use. These products conform to published specifications, if any, and the products are merchantable. Test data contained herein is believed to be reliable but unless specifically stated are not to be taken as specifications for products.