

4920 Commerce Parkway #11  
Cleveland, OH 44122

P. 888-888-TAPE  
www.capitaltape.com

F. 877-893-3337



### Butyl Tapes

#### TECHNICAL DATA:

Base Polymer		Butyl Rubber PIB
Solids Content	ASTMC681	100% Solids / No Asbestos
VOC Content	ASTM D3960	0%
Cure Time		Fully cured before application
Tack Free Time		Non-Drying
Hardness	ASTM C661	20 Durometer, Shore A @ 77°F
Shrinkage	ASTM C771	None
Sag or Flow		None
Application Temperature Range		
	ASTM C603	Series 20°F to 140°F
Service Temperature Range		
	ASTM C1257	-45°F to 250°F
Shrinkage		None
Adhesion		Excellent for metal, wood, glass and masonry surfaces
Shelf Life		One year guarantee
Paint time		Do not paint
Colors:		Black Only
AAMA Verified Component		AAMA 804.3, 807.3

No warranties are made in this product information sheet. All statements, technical information and recommendations contained herein are based on tests believed to be reliable, but the accuracy and completeness thereof is not guaranteed. The sole obligation of seller and manufacturer shall be to replace any quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, indirect or consequential, arising out of the use of the product or the inability to use the product. Before using, user shall determine the suitability of the product for user's intended use, and user assumes all risk and liability whatsoever in connection therewith.