

**Capital Tape Co, Inc**  
**4920 Commerce Parkway #11**  
**Cleveland, OH 44128**  
**Fax: 887-893-3337**



## **CT4725B**

An acrylic foam with high tack and shear strength; excellent resistance to solvents, chemicals, UV and heat; gray with a red plastic release liner.

Applications include :

- Car side molding, emblem and exterior decoration mounting
- High performance mounting of plastic strips, trims and nameplates

### **PHYSICAL PROPERTIES**

Thickness:	25 mils
180° Peel Adhesion:	4.6kg / 25mm (10.1# / inch) Jaw separation of 12"(30.5cm)/ min after dwell of 24 hours at room temperature
Heat Resistance:	120°C (248°F) sample conditioned at 40°C (105°F) for one hour and temperature raised 3°C every 5 minutes with 500 gm load. Tape size: 20mm x 20mm
Normal Tensile Strength:	40.9kg / 25.4mm x 25.4mm (90# per inch <sup>2</sup> ) 24 hour dwell, jaw separation of 200mm (8") per minute at room temperature

These are approximate values and do not constitute a warranty. It is the customer's responsibility to determine these products fitness for use in the intended end use application. Test data contained herein is believed to be reliable and it is not stated as, or to be taken as, a specification.