

Capital Tape Co, Inc
4920 Commerce Parkway #11
Cleveland, OH 44128
Fax: 887-893-3337



CVT636
Colored Vinyl Tapes (Matte Surface-Soft PVC)

Used for color coding, lane marking and safety coding to meet OSHA requirement; decorating striping on vehicles, boats sporting equipment, etc., masking for hard chrome plating and anodizing; harness and pipe wrapping; duct and joint sealing.

Product features a long shelf life and "write-on" capability. It provides a very effective vapor and moisture barrier. Highly conformable and resistant to aging, sun, water, fungus, bacteria, oil, acids, alkalies and corrosive chemicals. Provides good abrasion, impact and rupture resistance.

14 OSHA Colors available: Yellow, White, Black, Clear Red, Orange, Dark Blue, Light Blue, Gray, Purple, Dark Brown, Medium Brown, Dark Green and Light Green

PHYSICAL PROPERTIES:

Adhesive:	Rubber Resin
Total Thickness:	6 mils (0.15mm)
Adhesion:	22 oz./inch
Tensile Strength:	16 lbs/inch
Elongation	150% at break
Temperature Resistance	-20°F to 176°F
Moisture Vapor Transmission:	Less than 2.5% (Gm/100 sq in/24 hours)
Metal Corrosion:	None to Copper, Brass, Steel, Aluminum
Accelerated Aging Factor:	Greater than 100% (% of original adhesion to backing after aging)
Government Specifications:	Conforms to PPP-T-66E, Type I, Class 2; MIL-T-4239a (black only); A-A-1689A

NOTE: Performance data indicates average production values and should not be used for minimum specification values. The customer is advised to fully determine the suitability of these products for his intended use. Test data contained herein is believed to be reliable and it is not stated as, or to be taken as, a specification for these products.