

**Capital Tape Co, Inc**  
**4920 Commerce Parkway #11**  
**Cleveland, OH 44128**  
**Fax: 887-893-3337**



## **KC 1724**

1/16" high density, micro-cellular open cell urethane foam carrier coated on one side with a high performance, permanent, acrylic adhesive.

### **PHYSICAL PROPERTIES**

Thickness		single coated .062"
Density, ASTM D-1667		25 lbs./cu.ft.
Hardness, Shore A	ASTM D-2240	25
Tensile Strength	ASTM D-882	80 p.s.i.
100% modulus	ASTM D-882	50 p.s.i.
Elongation	ASTM D-882	200% p.s.i.
Thermal Conductivity ASTM C-177		.59 Btu/(hr)(ft <sup>2</sup> )(°F/in.)
Dynamic tensile bond		60 p.s.i.
Dynamic shear adhesion		40 p.s.i.
180° Peel adhesion from Stainless Steel		
1 hour dwell	Liner Side	100 oz./in.
1 hour dwell	Exposed Side	80 oz./in.

These are approximate values and do not constitute warranty that products are fit for a particular purpose. The customer is advised to fully determine the suitability of these products for his intended use. These products conform to published specifications, if any, and the products are merchantable. Test data contained herein is believed to be reliable but unless specifically stated are not to be taken as specifications for products.