

**Capital Tape Co, Inc**  
**4920 Commerce Parkway #11**  
**Cleveland, OH 44128**  
**Fax: 887-893-3337**



### V1520 Medium Density PVC Foam

Aggressive, pressure-sensitive adhesive on both sides of a medium density foam. These tapes provide an excellent combination of light density flexibility with heavy density strength. Tested and approved to AAMA 810.1-92 expanded cellular glazing tapes. Excellent for use in glazing applications. maintains a seal in high movement joints and effectively functions as a thermal break and insulator.

**PHYSICAL PROPERTIES:**

Density (lbs./cu. ft.)	ASTM D-1667	15#
Hardness (Shore 00)	ASTM D-2240	40
Force to Compress (psi) kPa	ASTM D-1667	9 @25% 62
Compression Set 30% (% loss from original height)	ASTM D-1667	2
Water absorption (% by volume)	GTP	1.0
Tensile Strength (psi) kPa	ASTM D-412	80 550
Percent Elongation	ASTM D-412	160
Thermal Conductivity (K factor) (btu-in.)/(hr.,sq.ft.)(F°) w.mK	ASTM C-518	0.30
Recommended Service Temperature		-30°F to 200°F -35°C to 90°C
Recommended Application Temperature		50°F to 110°F 10°C to 45°C
Fungi resistance	Excellent	
Oxidation resistance	Excellent	
Weather resistance	Excellent	

The values stated in charts are averages and are not to be construed as a warranty. Products must be tested by the end user for suitability in their applications.

*Information provided by Gaska Tape*