

**Capital Tape Co, Inc**  
**4920 Commerce Parkway #11**  
**Cleveland, OH 44128**  
**Fax: 887-893-3337**



## **V1526 Series – Vinyl Glazing Foams**

Aggressive, pressure sensitive adhesive on both sides of a medium density foam. These tapes provide an excellent combination of light density flexibility with heavy density strength. Products feature an easy release film liner.

Tested and approved to AAMA 810.1-92 expanded cellular glazing tapes; these foams are silicone compatible.

- Excellent in glazing applications
- Maintains a seal in high movement joints
- Effectively functions as a thermal break and insulator
- Excellent resistance to fungi, oxidation, and weather

### **PHYSICAL PROPERTIES:**

Density	ASTM D-1667	15 lbs./cu.ft.
Hardness (Shore OO)	ASTM D-2240	40
Force to compress 25%	ASTM D-1667	9 p.s.i.
Compression Set 30% (% loss from original height)	ASTM D-1667	2
Water absorption (% by volume)		1.0
Tensile strength	ASTM D-412	80 p.s.i.
Percent elongation	ASTM D-412	160
Thermal conductivity (K factor) (btu-in.)/(hr.sq.ft.) (F°)	ASTM C-518	0.30
Recommended Service Temperature:		-30°F to 200° F -35°C to 90° C
Recommended Application Temperature:		50° F to 110° F 10° C to 45° C

These are approximate values and do not constitute a warranty. It is the customer's responsibility to determine these products fitness for use in the intended end use application. Test data contained herein is believed to be reliable and it is not stated as, or to be taken as, a specification for these products.