

**Capital Tape Co, Inc.**  
**4920 Commerce Parkway #11**  
**Cleveland, OH 44128**  
**Fax: 887-893-3337**



## V990 Medium Density PVC Foam

Closed cell pvc with pressure sensitive adhesive on two sides and protected by a plastic liner. Effective glazing sealant for most residential wood, PVC, aluminum or FRP window designs. Effectively reduces sound transmission while sealing out dust, water, wind and light. Excellent resistance to weathering, oxidation and ultraviolet exposure produces long-life seal.

### PHYSICAL PROPERTIES:

Density	ASTMD-1667	15
Force to compress (PSI)*	AAMA 810.1	8.9
Compression Deflection (PSI)*	AAMA 810.1	6.6
Compression Set (%)*	AAMA 810.1	5.4
Water Absorption (% by weight)*	AAMA 810.1	1.8
Water Penetration (%)	AAMA 810.1	<1
Pump Test	AAMA 810.1	Pass
Tensile Adhesion (PSI)	AAMA 810.1	80
Tensile Elongation (%)	AAMA 810.1	190
Peel Adhesion (lbs./in.)	AAMA 810.1	10.2
Recommended Service Temperature:	-30° F to 180°F	
Recommended Application Temp.:	45°F Minimum	

\*\*It is strongly recommended the product be tested under individual application conditions/use prior to use. The product contains plasticizer which may adversely affect some plastics.

\*Based on 25% compression

For a period of 6 months from the date of first sale this product is warranted to be free from defects in material and workmanship. The only obligation of the manufacturer will be to replace any portion proving defective, or at their option, to refund the purchase price thereof. The warranty is in lieu of the warranties of merchantability, fitness for particular purpose, and all other warranties, expressed or implied. No deviation is authorized.