

Capital Tape Co, Inc
4920 Commerce Parkway #11
Cleveland, OH 44128
Fax: 216.292.3435



9230EZ Performance Mounting Tape – Green Liner

High performing solvent-based acrylic adhesive system coated on each side of a black foam carrier and protected by an "easy release" green PE liner. This product has very high shear strength and is highly resistant to solvents, chemicals, UV and heat. It also exhibits weather and age resistance making it suitable for outdoor applications.

Some applications include:

- Aftermarket automotive industry applications (i.e. car side molding)
- Mount of mirror tiles and labels

Physical properties:

Thickness:	.030" / 30 mil
Peel Adhesion:	1.4 kg/25mm PSTC-3
Shear Strength:	Over 24 hrs with 35.3 oz loading on 1" x 1" (1.0 kg/25mm x 25mm) bonding 2 stainless steel plates at 77°F (25°C)
Heat Resistance:	Over 24 hrs with 17.6 oz loading on 1" x 1" (0.5 kg/25mm x 25mm) bonding 2 stainless steel plates at 176°F (80°C)
Normal Tensile Strength:	over 99 lbs. / 25 mm x 25 mm
Service Temperature:	-40°F - 248°F (-40°C ~ 120°C)

For best results, store this product at 72°F (22°C) and 50% relative humidity. Shelf life = 2 years.

These are approximate values and do not constitute a warranty. It is the customer's responsibility to determine these products fitness for use in the intended end use application. Test data contained herein is believed to be reliable and it is not stated as, or to be taken as, a specification of these products.