

Capital Tape Co, Inc
4920 Commerce Parkway #11
Cleveland, OH 44128
Fax: 216.292.3435



9241 Performance Mounting Tape

High performing, solvent-based, acrylic adhesive system coated on each side of a cross-linked, black polyethylene foam carrier and protected by a red plastic liner. This foam tape has high shear strength and is highly resistant to solvents, chemicals, UV and heat. This makes it suitable for outdoor applications.

Some applications include:

- Car side molding, emblem, and exterior decoration mounting
- Bonding of plastic strips, trims, and nameplates

Physical properties:

Thickness:	.040" / 40 mil	
Loop Tack:	140.8 oz. / 25mm	FINAT-9
Peel Adhesion:	65.1 oz./in.	PSTC-3
Shear Strength:	Over 24 hrs with 35.2 oz loading on 1" x 1" (1.0 kg/25mm x 25mm) bonding 2 stainless steel plates at 77°F (25°C)	
Heat Resistance:	Over 24 hrs with 17.6 oz loading on 1" x 1" (0.5 kg/25mm x 25mm) bonding 2 stainless steel plates at 176°F (80°C)	
Normal Tensile Strength:	Over 44 lb/1" x 1" (20kg/25mm x 25mm)	
Service Temperature:	-4°F ~ 194°F (-20°C ~ 90°C)	

For best results, store this product at 72°F (22°C) and 50% relative humidity. Shelf life = 2 years.

These are approximate values and do not constitute a warranty. It is the customer's responsibility to determine these products fitness for use in the intended end use application. Test data contained herein is believed to be reliable and it is not stated as, or to be taken as, a specification of these products.