


CT1826


SILICONE-COMPATIBLE STRUCTURAL SPACER TAPE

CapitalTape
A family business, since 1990


CATEGORY




STRUCTURAL SPACER



COMPRESSIBLE GLAZING



WEATHERSTRIPPING



RESIDENTIAL GLAZING



ULTRA HIGH-BOND



PE MOUNTING

INDUSTRY

AUTOMOTIVE

RECREATIONAL VEHICLES

GLAZING

CONSTRUCTION DETAILING

GASKETING

ACOUSTICS

LOG HOME

MOUNTING

PROTECTIVE

TAPE OVERVIEW

A silicone-compatible structural spacer tape, the CT1826 from Capital Tape is used within curtain wall systems to provide security and a barrier between the glass and frame. The CT1826 tape is very tough, very dense, and virtually invincible. Available in black.

- Double-sided adhesive
- Ideal for curtain wall structural silicone
- Great for any application that relies on costly, high-density urethane gasketing for spacing, vibration, dampening or cushioning
- Excellent adhesion to stainless steel, glass, aluminum, painted metal, vinyl



SCAN FOR MORE

Visit this product page, request samples, or get an online quote.

TAPE PROPERTIES

The values stated in charts are averages and are not to be construed as a warranty. Products must be tested by end user for application suitability.

Density	ASTM D-1667	31.10 lbs./cu. ft.
Hardness (Type OO Durometer)	ASTM D-2240	87
Force to Compress (@ 10%)	ASTM D-1667	29.0 PSI
Compression Set (@ 10%)	ASTM D-1667	36.6%
Tensile Strength	ASTM D-412	25 PSI
Percent Elongation	ASTM D-412	188%
Thermal Conductivity	ASTM C-518	0.575 btu-in/(hr-ft ² -°F)
Recommended Service Temp. 12 month shelf life	-10°F to 200°F -23°C to 100°C	
Recommended Application Temperature	50°F to 110°F 10°C to 45°C	
Fungi resistance	Good	
Oxidation resistance	Good	
Weather resistance	Good	

MEMBER
NGA
NATIONAL GLASS ASSOCIATION

FMVSS 302A
Federal Motor Vehicle Safety
Standard No. 302
CAPITAL TAPE

A.A.M.A.
CERTIFIED
810.1-16 Type I

WE CUT TAPE.

Learn more at capitaltape.com

1-888-888-TAPE

service@capitaltape.com

4920 Commerce Parkway #11, Cleveland, OH 44128