


CT3200 SERIES


OPEN-CELL POLYURETHANE STRUCTURAL SPACER TAPE

CapitalTape
A family business, since 1990


CATEGORY




STRUCTURAL SPACER



COMPRESSIBLE GLAZING



WEATHERSTRIPPING



RESIDENTIAL GLAZING



ULTRA HIGH-BOND



PE MOUNTING

INDUSTRY

AUTOMOTIVE

RECREATIONAL VEHICLES

GLAZING

CONSTRUCTION DETAILING

GASKETING

ACOUSTICS

LOG HOME

MOUNTING

PROTECTIVE

TAPE OVERVIEW

The CT3200 Series is an open-cell, semi-rigid polyurethane foam spacer tape, ideal for two- and four-sided structural glazing systems. The CT3200 Series is compatible with all silicone, providing excellent resistance to oxidation, fungi, and temperature extremes.

- Features easy release liner
- Ideal for curtain wall structural silicone
- Great for any application that relies on costly, high-density urethane gasketing for spacing, vibration, dampening or cushioning
- Excellent adhesion to stainless steel, glass, aluminum, painted metal, vinyl



SCAN FOR MORE

Visit this product page, request samples, or get an online quote.

TAPE PROPERTIES

The values stated in charts are averages and are not to be construed as a warranty. Products must be tested by end user for application suitability.

Density	ASTM D-1667	22.63 lbs./cu. ft.
Hardness (Type OO Durometer)	ASTM D-2240	83
Force to Compress (@ 10%)	ASTM D-1667	30.8 PSI
Compression Set (@ 10%)	ASTM D-1667	6.3%
Tensile Strength	ASTM D-412	18.6 PSI
Percent Elongation	ASTM D-412	162%
Thermal Conductivity	ASTM C-518	0.55 btu·in/(hr·ft ² ·°F)
Recommended Service Temp. 12 month shelf life	-40°F to 180°F -40°C to 82°C	
Recommended Application Temperature	60°F to 125°F 16°C to 52°C	
Fungi resistance	Good	
Oxidation resistance	Good	
Weather resistance	Good	

MEMBER
NGA
NATIONAL GLASS ASSOCIATION

FMVSS 302A
Federal Motor Vehicle Safety
Standard No. 302
CAPITAL TAPE

A.A.M.A.
CERTIFIED
810.1-16 Type I

WE CUT TAPE.

Learn more at capitaltape.com

1-888-888-TAPE

service@capitaltape.com

4920 Commerce Parkway #11, Cleveland, OH 44128